

Marca: Publistock
 Modelo: pitch 2.6 mm



1. LED					
LED parameters	Package	Colour	Wavelength	View Angle	Test Cond.
	3in1 SMD1415	Red	620~625nm	140°/140°	25℃,20mA
		Green	520~525nm	140°/140°	25℃,20mA
		Blue	465~467nm	140°/140°	25℃,20mA
2. Module					
Part Number	Customerized P2.6	Module Picture	Cabinet Picture (aluminum)		
Pixel Pitch	2.6mm				
LED arrangement	SMD1415				
Physical Density	147456 pixels/m2				
Resolution	96(w) x 96(h)				
Module Size (w*h)	250mm x 250mm				
3. Panel					
Size (w*h)	500mmx 500mm				
Resolution	192(w) x192(h)				
Quantity(modules)	2pcs(w) x 2pcs(h)				
Panel Weight	about 7kg				
Brightness	around 4500 cds/m²				
Max. Power	620w/panel				
Ave. Power	300w/panel				
Material	Aluminum				
4. Proposal Screen Specification					

Screen Size	12sqm	Driving Method	1/16 scan
LED lamp	HONGSHENG LED	View Angle	160°/160°
Controlling system	NOVA	Viewing Distance	4m - 50m
Control method	SYNCHRONOUS	Refresh frequency	7680Hz
Drive Chip	FM6373	Gamma Correction	10 Levels
Input Voltage	AC220V, 50~60HZ	Screen Color	16.7m
Protective Grade	IP65	Grey Scale	14 bits/16384levels
Control Distance	Cat5 120m/Optical fiber 15km	Operating Life	100,000 hours
Operating Temp	-10℃~+45℃	MTBF	10,000 hours
Operating Humidity	10-90%RH	Defects Rate	≤0.02%